

Outdoor unit	RXA35A2V1B
Indoor unit	FTXA35A2V1BW

<b>Function</b>		<b>Heating season</b>	
Cooling	Yes	Average (mandatory)	Yes
Heating	Yes	Warmer (if designated)	Yes
		Colder (if designated)	No

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Design Load</b>				<b>Seasonal efficiency</b>			
Cooling	Pdesignc	3.40	kW	Cooling	SEER	8.73	-
heating / Average	Pdesignh	2.50	kW	heating / Average	SCOP / A	5.15	-
heating / Warmer	Pdesignh	2.00	kW	heating / Warmer	SCOP / W	6.28	-
heating / Colder	Pdesignh		kW	heating / Colder	SCOP / C		-

<b>Declared capacity* for cooling, at indoor temperature 27(19) °C and outdoor temperature Tj</b>				<b>Declared energy efficiency ratio*, at indoor temperature 27(19) °C and outdoor temperature Tj</b>			
Tj = 35 °C	Pdc	3.40	kW	Tj = 35 °C	EERd	4.37	-
Tj = 30 °C	Pdc	2.51	kW	Tj = 30 °C	EERd	6.28	-
Tj = 25 °C	Pdc	1.61	kW	Tj = 25 °C	EERd	10.58	-
Tj = 20 °C	Pdc	1.33	kW	Tj = 20 °C	EERd	16.21	-

<b>Declared capacity* for heating / Average season , at indoor temperature 20 °C and outdoor temperature Tj</b>				<b>Declared coefficient of performance* / Average season, at indoor temperature 20 °C and outdoor temperature Tj</b>			
Tj = -7 °C	Pdh	2.21	kW	Tj = -7 °C	COPd	3.58	-
Tj = 2 °C	Pdh	1.35	kW	Tj = 2 °C	COPd	5.19	-
Tj = 7 °C	Pdh	0.94	kW	Tj = 7 °C	COPd	6.19	-
Tj = 12 °C	Pdh	1.10	kW	Tj = 12 °C	COPd	7.97	-
Tj = bivalent temperature	Pdh	2.21	kW	Tj = bivalent temperature	COPd	3.58	-
Tj = operating limit	Pdh	2.62	kW	Tj = operating limit	COPd	2.30	-

<b>Declared capacity* for heating / Warmer season , at indoor temperature 20 °C and outdoor temperature Tj</b>				<b>Declared coefficient of performance* / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj</b>			
Tj = 2 °C	Pdh	2.00	kW	Tj = 2 °C	COPd	4.64	-
Tj = 7 °C	Pdh	1.29	kW	Tj = 7 °C	COPd	6.11	-
Tj = 12 °C	Pdh	1.1	kW	Tj = 12 °C	COPd	7.97	-
Tj = bivalent temperature	Pdh	2.00	kW	Tj = bivalent temperature	COPd	4.64	-
Tj = operating limit	Pdh		kW	Tj = operating limit	COPd	2.30	-

<b>Declared capacity* for heating / Colder season , at indoor temperature 20 °C and outdoor temperature Tj</b>				<b>Declared coefficient of performance* / Colder season, at indoor temperature 20 °C and outdoor temperature Tj</b>			
Tj = -7 °C	Pdh		kW	Tj = -7 °C	COPd		-
Tj = 2 °C	Pdh		kW	Tj = 2 °C	COPd		-
Tj = 7 °C	Pdh		kW	Tj = 7 °C	COPd		-
Tj = 12 °C	Pdh		kW	Tj = 12 °C	COPd		-
Tj = bivalent temperature	Pdh		kW	Tj = bivalent temperature	COPd		-
Tj = operating limit	Pdh		kW	Tj = operating limit	COPd		-
Tj = -15 °C	Pdh		kW	Tj = -15 °C	COPd		-

<b>Bivalent temperature</b>				<b>Operating limit temperature</b>			
heating / Average	Tbiv		°C	heating / Average	Tol	-15	°C
heating / Warmer	Tbiv	2	°C	heating / Warmer	Tol		°C
heating / Colder	Tbiv		°C	heating / Colder	Tol		°C

<b>Cycling interval capacity</b>				<b>Cycling interval efficiency</b>			
for cooling	Pcycc		kW	for cooling	EERcyc		-
for heating	Pcych		kW	for heating	COPcyc		-
Degradation co-efficient cooling**	Cdc	0.25	-	Degradation co-efficient cooling**	Cdh	0.25	-

<b>Electric power input in power models other than 'active mode'</b>				<b>Annual electricity consumption</b>			
off mode	Poff	5.0E-4	kW	Cooling	QCE	137	kWh/a
standby mode	Psb	5.0E-4	kW	heating / Average	QHE	680	kWh/a
thermostat-off mode	Pto	0.007	kW	heating / Warmer	QHE	446	kWh/a
crankcase heater mode	PCK	0.0	kW	heating / Colder	QHE		kWh/a

<b>Capacity control</b>				<b>Other items</b>			
fixed	N			Sound power level (indoor/outdoor)	LWA	60 / 61	db(A)
staged	N			Global warming potential	GWP	675.0	kgCO <sub>2</sub> eq.
variable	N			Rated air flow (indoor/outdoor)		11.9 / 36.0	m <sup>3</sup> /min

<b>Contact details for obtaining more information</b>	DAIKIN EUROPE N.V. Zandvoordestraat 300 B-8400 Oostende Belgium
---	--

\* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'Declared EER/COP' of the unit.  
 \*\* if default Cd = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating of cooling cycling test value is required.